

SHORT ON SPACE BUT NOT ON COLOUR.



DIGITAL OULDUR SYSTEM CDC 5526L/5626L

DIGITAL MULTIFUNCTIONAL COLOUR SYSTEM CDC 5526L/5626L

THIS COLOURFUL AND COMPACT HELPER WILL FIT WITH ANY ORGANISATION – **NO MATTER HOW SMALL THE SPACE.**



HIGH-QUALITY COLOUR PRINTS ARE A MUST, BUT YOU DO NOT HAVE ENOUGH SPACE TO SET UP A LARGE SYSTEM? IF THIS DESCRIBES YOUR SITUATION, THE A4 COLOUR MULTIFUNCTIONAL SYSTEMS CDC 5526L AND CDC 5626L ARE PRECISELY WHAT YOU NEED: THEY OFFER A BROAD RANGE OF FUNCTIONS FOR SMALL TEAMS AND TASK GROUPS WITHOUT TAKING UP A LOT OF SPACE.

The CDC 5526L is a 3-in1 system that produces colour copies, colour printouts and colour scans. The CDC 5626L 4-in-1 version has one more feature: a complete office fax system. Besides this difference, the systems have many specifications in common, such as the productive printing speed of 26 A4 pages per minute (or 13 A4 pages in duplex mode) either in colour or b/w.

The original feeder with auto reverse function that holds up to 50 documents, a duplex mode for papersaving, two-sided printing and a network function are standard features of both systems. When it comes to scanning, there are many useful functions such as Scan to PC, Scan to e-mail, Scan to FTP, Scan to USB and TWAIN and WIA scan. Moreover, the paper capacity of 300 sheets can be expanded to 1,300 sheets for interruption-free printing of formats from A6R to A4. The system memory of 768 MB RAM, upgradable to max 1,792 MB RAM, further ensures smooth runnings. In addition, you can add an optional Card Authentication Kit to your CDC 5526L or CDC 5626L to protect the system and printouts from unauthorised access. Quite plainly, small can sometimes be very large indeed!



PLENTY OF COLOURS INSTEAD OF **BLACK ON WHITE MONOTONY.**

CDC 5526L: Colour copier, printer, scanner/CDC 5626L: Colour copier, printer, scanner, fax; both units come with a document feeder, duplex mode, 1 x 250 sheet universal cassette and 50 sheet multi-bypass

- Excellent colour quality for office applications (images, presentations, handouts), if required also in b/w
- High scanning throughput of up to 35 A4 sheets in b/w or up to 25 A4 sheets in colour
- Well-designed control panel for ease of operation
- 'ID card copy' program function, additional program procedures can be saved, incl. addresses or mailing lists
- USB host for direct scanning to and printing from a USB stick
- High max paper capacity of 1,300 sheets, paper weights of up to 220 g/m²
- Optional multi-purpose cassette for special media







*option / **option without illustration

original tester with a to reverse function

Wat at one steel une sal case te

ormultiouropecasete for the

Card Puttenication Viel BY*.

DIGITAL 🤤 🔍 🌢 MULTIFUNCTIONAL COLOUR SYSTEM CDC 5526L/5626L

IF IT WORX, IT'S

GENERAL

Туре	Desktop
Function	CDC 5526L: Copy, print, scan
	CDC 5626L: Copy, print, scan, fax
Print technology	Laser colour and b/w
Original format	max A4 from platen glass
Original feeder	50 sheet A4 (standard), 50–120 g/m ² (simplex),
	50–110 g/m² (duplex)
Copy/print speed	max 26 A4 pages/min and duplex: max 13 A4 pages/min in
	colour and b/w
1st page	Colour: 12 seconds, b/w: 10 seconds (copy)*,
	colour: 10.5 seconds, b/w: 9 seconds (print)*
Warm-up time	29 seconds
Copy resolution	600 x 600 dpi
Greyscales	256
Paper feed	1 x 250 sheet universal cassette (A6R–A4), 50 sheet multi-
	bypass (A6R–A4 [min 70 x 148 mm, max 216 x 356 mm])
Paper weights	Universal cassette 60–163 g/m ² , multi-bypass 60–220 g/m ² ,
	duplex 60–163 g/m ²
Paper output	150 sheet A4
System memory	768 MB RAM, 1,792 MB RAM
Continuous copying	1–999 copies
Zoom	25 %-400 % in steps of 1 %
Functions	Duplex, job reservation, job programs, ID card copy, scan
	once - copy many, continuous scan, N-up,
	20 management codes

ENVIRONMENT Ma

Po

N

Туре Prin Prin Proc

Inter Netv Oper Emu Fund

Sc

Sc

Sc

S

Sc Fil Int Ne 00 Fu

ains voltage	220/240 V, 50/60 Hz
ower consumption	approx. 1,187/1,195 W (CDC 5526L/5626L) max, approx.
	470/479 W (CDC 5526L/5626L) in operation, approx. 79 W
	in stand-by mode, approx. 16/17 W (CDC 5526L/5626L)
	in sleep mode
oise level	approx. 48.3/48.5 (CDC 5526L/5626L) dB(A) in operation,
	approx. 28.4 dB(A) in stand-by mode (ISO 7779/9296)
afety	GS/TÜV, CE

PRINT SYSTEM

2	Integrated within the system
t format	A6R-A4
t resolution	600 x 600 dpi
essor	PowerPC 464/667 MHz
rfaces	USB 2.0, 10/100BaseTX, USB host (2), CF slot
vork protocols	TCP/IP, IPX/SPX, Net BEUI, EtherTalk
rating systems	Windows 2000, XP, Vista, Windows 7, Server
	2000/2003/2008 R2, Novell NetWare, Linux, Mac ex OS 10.4
Ilations	PCL6, KPDL 3 (PostScript 3 compatible), XPS,
	PRESCRIBE IIc, PDF 1.5
ctions	Colour Optimiser, USB direct printing, printing of e-mails,
	private printing (with additional memory), barcode printing,
	WSD/internet printing

DIMENSIONS/WEIGHT

Dimensions Weight

580 x 514 x 550 mm (H x W x D)

approx. 37 kg

Your UTAX dealer

SCAN SYSTEM

an type	CCD colour and b/w
an format	max A4
an speed	Colour: max 25/13 A4 originals/min (simplex/duplex) with
	300 dpi, b/w: max 35/18 A4 originals/min (simplex/duplex)
	with 300 dpi
an resolution	200 dpi, 300 dpi, 400 dpi, 600 dpi
an mode	Photo, text, photo/text, OCR
le types	TIFF, PDF (1.4/A), JPEG, XPS
terface	10/100BaseTX
etwork protocol	TCP/IP
perating system	s Windows XP, Vista, Windows 7, Server 2003/2008 R2
Inctions	Scan to SMB, scan to e-mail, scan to FTP, scan to USB,
	TWAIN scan, WIA scan (Windows Vista, Windows 7,
	Server 2008 R2), SMTP authentication, LDAP

FAX SYSTEM (CDC 5626L ONLY)

Compatibility	Super G3
Original format	max A4
Modem speed	33.6 kbps
Transmission speed	3 seconds or less using JBIG
Compression method	JBIG, MMR, MR, MH
Fax resolution	Standard (200 x 100 dpi), fine (200 x 200 dpi), super fine (200 x 400 dpi), ultra fine (400 x 400 dpi)
Fax memory	4 MB
Abbreviated dial	100 numbers
One touch dial	22 numbers
Group dial	50 numbers
Operating systems	Windows XP, Vista, Windows 7, Server 2003/2008 R2
Functions	Network fax driver, automatic redialling, delayed transmission

OPTIONS

Paper feed	max 2 x PF-520 (500 sheet universal cassette [A5R-A4,
	60–163 g/m²]), max 2 x PF-530 (500 sheet multi-purpose
	cassette [A5R-A4, 60-220 g/m²])
Other options	Card authentication kit (B), UG-33 ThinPrint® kit, UT-110G
	Gigabit Ethernet card, cabinet no. 61

*Depending on operating status.

Specifications subject to change without notice. Image shows machine with optional accessories. The CDC 5526L and the CDC 5626L are manufactured in accordance with the requirements of the Energy Star Program.

Since 1961 UTAX GmbH has been a brand for professional office technology. As



UTAX recommends the use of original UTAX accessories for trouble-free operation of your system. For recommended print media refer to the user manual. UTAX and the UTAX logo are registered trademarks of UTAX GmbH. All other brand names referred to are registered trademarks of the respective manufacturers.