

# TECHNICAL DATA

### ENVIRONMENT

Mains voltage Power consumption

Paper feed

Other options

220/240 V. 50 Hz LP 3135: approx. 543.6 W in operation, approx. 80.1 W in stand-by

mode, approx. 4.3 W in sleep mode

LP 3335: approx. 553.9 W in operation, approx. 89.3 W in stand-by mode, approx. 5.5 W in sleep mode

Noise level approx. 55 dB(A) in operation, approx. 30 dB(A) in stand-by mode (ISO 7779/9296)

GS/TÜV. CE Safety

### CONSUMABLES

Toner for 7,200 A4 pages according to ISO 19752, starter kit for 2,300 A4 pages according to ISO 19752

#### OPTIONS

max 2 x PF-100 (250 sheet universal cassette (A4-A5)) Network card UT-110G, cabinet no. 59



## GENERAL

Type Desktop Function Print Print technology Laser b/w Print format A4-A6R, max 215.9-356 mm, min 70-148 mm

Print speed max 35 A4 pages/min, max 19 A4 pages/min duplex

1st page/warm-up time 7 seconds\*, 19 seconds Print resolution LP 3135: 600 x 600 dpi, LP 3335: 1.200 x 1.200 dpi

> Paper feed 1 x 250 sheet universal cassette (A4-A6R).

> > LP 3335: PowerPC440F5/500 MHz

50 sheet multi-bypass (A4-A6R) Universal cassette 60-120 g/m², multi-bypass 60-220 g/m², Paper weights

duplex 60-105 g/m<sup>2</sup>

Paper output 250 sheet A4, 200 sheet A4 duplex Processor LP 3135: PowerPC405F5/360 MHz.

Print memory LP 3135: 32 MB RAM (max 544 MB RAM - 1 slot),

LP 3335: 128 MB RAM (max 1,152 MB RAM - 1 slot)

USB 2.0, CF slot (LP 3135: 1 slot, LP 3335: 2 slots), Interfaces USB host (LP 3335), 10/100BaseTX (standard with

LP 3335, optional for LP 3135)

Operating systems Windows 2000, XP, Vista, Windows 7, Server 2003/2008,

Novell NetWare\*\*. Mac ex OS 10.X

PCL6, KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe,

Line Printer, Diablo 630, IBM Proprinter X24E, Epson LQ-850,

(PDF-1.5, XPS - LP 3335 only)

Printing of e-mails\*\*, barcode printing, network data encryption (SSL)\*\* Functions

### **DIMENSIONS/WEIGHT**

Dimensions LP 3135: 250 x 375 x 393 mm (H x W x D),

\*depending on operating status.

\*\*with optional network card for LP 3135.

LP 3335: 267 x 375 x 393 mm (H x W x D)

Weight approx. 12 kg

in accordance with the requirements of the ENERGY STAR Program. UTAX recommends the use of original UTAX accessories for trouble-free operation of your system. For recommended print media refer to the user manual.

Specifications subject to change without notice.

Image shows machine with optional accessories.

Your UTAX dealer



The LP 3135 and the LP 3335 are manufactured

sharp printing every time.

05/2010

Following in-depth analysis of all output systems used in the company, with our UTAX DOCUMENT CONSULTING sales concept we create an offering precisely tailored to the customer's needs. Using the very latest UTAX digital systems in combination with practical software solutions from the DMS areas of archiving, form printing and accounting, the entire output and document management becomes extremely efficient and costs are reduced.

www.utax.com

UTAX and the UTAX logo are registered trademarks of UTAX GmbH. All other brand names referred to are registered trademarks of the respective manufacturers.

THESE TWO LOVE TO PRINT UNDER PRESSURE!

Reliable, productive, fast - these are the outstanding attributes of the LP 3135 and

LP 3335 network capable b/w printers, which will win everyone in your team over in no

time. They deliver the first page after only 7 seconds and a fast 35 A4 pages per minute

or 19 A4 pages per minute in standard duplex mode. With paper formats of A4-A6R, paper

weights of up to 220 g/m<sup>2</sup> and a max paper capacity of 800 sheets, almost any job can be

dealt with easily and quickly, and a print resolution of up to 1,200 x 1,200 dpi means pin

